



## Part Reference Guide

# DR0228T

### Applications

Manufacturer	Model	Series	Position
Shorts	100/200/C23/JC23	330	Main
Shorts	100/200/C23/JC23	360	Main
Shorts		Sherpa	Main
Fokker		F27	Main
Fokker		F50	Main

### Technical Data

Ply Rating	Speed Rating (MPH)	Max Load (lbs)	Tubed/Tubeless	Chined
12	190	13000	Tubeless	No

### Inflation & Dimensions

Size	34x10.75-16
Inflation Pressure Unloaded PSI	115
Inflation Pressure Loaded PSI	120
Inf Dim Width Shoulder	8.90
Inf Dim Width Max	10.45
Inf Dim Width Min	9.90
Inf Dim OD Min	33.65
Inf Dim OD Max	34.50
Inf Dim OD Shoulder	31.15
Rim Dim Width Between Flanges	8.25
Rim Dim Ledge Diameter	16
Rim Dim Flange Height	1.05
Rim Dim Min Ledge Width	1.85

### Approvals

QTR Number	1212
Test Spec	TSO-C62c
CAA EASA Approval	E14063 13/10/1988
FAA Approval	HH/VK/34/72:88 03/11/88
MOD Approval	DR0228T
NSN Approval	Not Declared
Civilian/Military	Civilian

