



## Part Reference Guide

# DR12325T

### Applications

| Manufacturer                    | Model | Series | Position |
|---------------------------------|-------|--------|----------|
| Bae Systems (British Aerospace) | 60    | Hawk   | Main     |

### Technical Data

| Ply Rating | Speed Rating (MPH) | Max Load (lbs) | Tubed/Tubeless | Chined |
|------------|--------------------|----------------|----------------|--------|
| 14         | 185                | 8300           | Tubeless       | No     |

### Inflation & Dimensions

|                                 |         |
|---------------------------------|---------|
| Size                            | 6.50-10 |
| Inflation Pressure Unloaded PSI | 160     |
| Inflation Pressure Loaded PSI   | 166     |
| Inf Dim Width Shoulder          | 5.65    |
| Inf Dim Width Max               | 6.65    |
| Inf Dim Width Min               | 6.25    |
| Inf Dim OD Min                  | 21.35   |
| Inf Dim OD Max                  | 22.10   |
| Inf Dim OD Shoulder             | 19.90   |
| Rim Dim Width Between Flanges   | 4.75    |
| Rim Dim Ledge Diameter          | 10      |
| Rim Dim Flange Height           | 0.81    |
| Rim Dim Min Ledge Width         | 1.30    |

### Approvals

|                   |                 |
|-------------------|-----------------|
| QTR Number        | 671             |
| Test Spec         | HS SPEC 32/2002 |
| CAA EASA Approval | Not Declared    |
| FAA Approval      | Not Declared    |
| MOD Approval      | DR12325T        |
| NSN Approval      | 2620-99-6115745 |
| Civilian/Military | Military        |