



Part Reference Guide

DR12668T

Applications

Manufacturer	Model	Series	Position
McDonnell Douglas		DC 9	Main
Boeing	100	737	Main
Boeing		720	Main
Airbus	B2	A300	Main
Airbus	B4	A300	Main
Airbus		A310	Main

Technical Data

Ply Rating	Speed Rating (MPH)	Max Load (lbs)	Tubed/Tubeless	Chined
24	225	27700	Tubeless	No

Inflation & Dimensions

Size	40x14
Inflation Pressure Unloaded PSI	170
Inflation Pressure Loaded PSI	178
Inf Dim Width Shoulder	12
Inf Dim Width Max	14
Inf Dim Width Min	13.25
Inf Dim OD Min	38.85
Inf Dim OD Max	39.80
Inf Dim OD Shoulder	35.10
Rim Dim Width Between Flanges	11
Rim Dim Ledge Diameter	16
Rim Dim Flange Height	1.63

Approvals

QTR Number	1202
Test Spec	TSO-C62c
CAA EASA Approval	E14000 15/06/1988
FAA Approval	HH/VK/7/13/2126:88 13/07/88
MOD Approval	DR12668T
NSN Approval	Not Declared
Civilian/Military	Civilian

Rim Dim Min Ledge Width	2.95
-------------------------	------