



Part Reference Guide

DR15348T

Applications

Manufacturer	Model	Series	Position
Boeing	200	747	Main
Boeing	300	747	Main
Boeing	Sp	747	Main
Airbus	B2	A300	Main
Airbus	B4	A300	Main
Airbus		A310	Main
Airbus		A320	Main

Technical Data

Ply Rating	Speed Rating (MPH)	Max Load (lbs)	Tubed/Tubeless	Chined
32	225	50400	Tubeless	No

Inflation & Dimensions

Size	49x17
Inflation Pressure Unloaded PSI	210
Inflation Pressure Loaded PSI	218
Inf Dim Width Shoulder	14.50
Inf Dim Width Max	17.25
Inf Dim Width Min	16.40
Inf Dim OD Min	47.70
Inf Dim OD Max	48.75
Inf Dim OD Shoulder	43
Rim Dim Width Between Flanges	13.25
Rim Dim Ledge Diameter	20

Approvals

QTR Number	1128
Test Spec	TSO-C62c
CAA EASA Approval	E13660 16/09/1986
FAA Approval	VK/9/8/2560:86 08/09/86
MOD Approval	DR15348T
NSN Approval	Not Declared
Civilian/Military	Civilian

Rim Dim Flange Height	1.88
Rim Dim Min Ledge Width	3.65