



Part Reference Guide

DR15842T

Applications

| Manufacturer | Model | Series | Position |
|---------------|-------|--------|----------|
| Airbus / Casa | | CN235 | Aux |

Technical Data

| Ply Rating | Speed Rating (MPH) | Max Load (lbs) | Tubed/Tubeless | Chined |
|------------|--------------------|----------------|----------------|--------|
| 12 | 160 | 7500 | Tubeless | No |

Inflation & Dimensions

| | |
|---------------------------------|--------|
| Size | 24x7.7 |
| Inflation Pressure Unloaded PSI | 115 |
| Inflation Pressure Loaded PSI | 120 |
| Inf Dim Width Shoulder | 6.75 |
| Inf Dim Width Max | 7.65 |
| Inf Dim Width Min | 7.20 |
| Inf Dim OD Min | 23.30 |
| Inf Dim OD Max | 24.15 |
| Inf Dim OD Shoulder | 21.50 |
| Rim Dim Width Between Flanges | 5.50 |
| Rim Dim Ledge Diameter | 10 |
| Rim Dim Flange Height | 0.91 |
| Rim Dim Min Ledge Width | 1.50 |

Approvals

| | |
|-------------------|--------------------------|
| QTR Number | 997 |
| Test Spec | TSO-C62c |
| CAA EASA Approval | E12827 15/03/1983 |
| FAA Approval | CC/3/23/1262/83 23/03/83 |
| MOD Approval | DR15842T |
| NSN Approval | Not Declared |
| Civilian/Military | Civilian |