



Part Reference Guide

DR17627T

Applications

Manufacturer	Model	Series	Position
Panavia		Tornado	Main
McDonnell Douglas		CF18	Main
McDonnell Douglas	Phantom	F4E	Main
McDonnell Douglas	Phantom	F4G	Main
McDonnell Douglas	Phantom	F4J	Main

Technical Data

Ply Rating	Speed Rating (MPH)	Max Load (lbs)	Tubed/Tubeless	Chined
24	250	25000	Tubeless	No

Inflation & Dimensions

Size	30x11.5-14.5
Inflation Pressure Unloaded PSI	245
Inflation Pressure Loaded PSI	255
Inf Dim Width Shoulder	10.20
Inf Dim Width Max	11.50
Inf Dim Width Min	11
Inf Dim OD Min	28.75
Inf Dim OD Max	29.75
Inf Dim OD Shoulder	27.60
Rim Dim Width Between Flanges	9.75
Rim Dim Ledge Diameter	14.50
Rim Dim Flange Height	1.25
Rim Dim Min Ledge Width	2.75

Approvals

QTR Number	1005
Test Spec	12620-45
CAA EASA Approval	Not Declared
FAA Approval	Not Declared
MOD Approval	DR17627T
NSN Approval	2620-21-8943905/-99-7899084
Civilian/Military	Military

