



Part Reference Guide

DR18426T

Applications

| Manufacturer | Model | Series | Position |
|--------------|-------|--------|----------|
| Eurocopter | | NH90 | Main |

Technical Data

| Ply Rating | Speed Rating (MPH) | Max Load (lbs) | Tubed/Tubeless | Chined |
|------------|--------------------|----------------|----------------|--------|
| 12 | 160 | 10725 | Tubeless | No |

Inflation & Dimensions

| | |
|---------------------------------|------------|
| Size | 615x225-10 |
| Inflation Pressure Unloaded PSI | 112 |
| Inflation Pressure Loaded PSI | 175 |
| Inf Dim Width Shoulder | 7.90 |
| Inf Dim Width Max | 9.50 |
| Inf Dim Width Min | 8.60 |
| Inf Dim OD Min | 23.75 |
| Inf Dim OD Max | 25.25 |
| Inf Dim OD Shoulder | 21.75 |
| Rim Dim Width Between Flanges | 7.87 |
| Rim Dim Ledge Diameter | 10 |
| Rim Dim Flange Height | 0.89 |
| Rim Dim Min Ledge Width | 1.61 |

Approvals

| | |
|-------------------|----------------|
| QTR Number | 1442 |
| Test Spec | TSO-C62d |
| CAA EASA Approval | Not Declared |
| FAA Approval | Not Declared |
| MOD Approval | DR18426T |
| NSN Approval | ZS324F1021200A |
| Civilian/Military | Military |