



Part Reference Guide

DR2212T

Applications

| Manufacturer | Model | Series | Position |
|--------------|-------|-------------|----------|
| Hindustan | | LCA (Naval) | Aux |

Technical Data

| Ply Rating | Speed Rating (MPH) | Max Load (lbs) | Tubed/Tubeless | Chined |
|------------|--------------------|----------------|----------------|--------|
| 12 | 218 | 5800 | Tubeless | No |

Inflation & Dimensions

| | |
|---------------------------------|-----------|
| Size | 19x6.25-9 |
| Inflation Pressure Unloaded PSI | 168 |
| Inflation Pressure Loaded PSI | 175 |
| Inf Dim Width Shoulder | 5.35 |
| Inf Dim Width Max | 6.27 |
| Inf Dim Width Min | 6.03 |
| Inf Dim OD Min | 19.10 |
| Inf Dim OD Max | 19.70 |
| Inf Dim OD Shoulder | 17.30 |
| Rim Dim Width Between Flanges | 5.38 |
| Rim Dim Ledge Diameter | 9 |
| Rim Dim Flange Height | 0.80 |
| Rim Dim Min Ledge Width | 2 |

Approvals

| | |
|-------------------|--------------|
| QTR Number | 1547 |
| Test Spec | Not Declared |
| CAA EASA Approval | Not Declared |
| FAA Approval | Not Declared |
| MOD Approval | DR2212T |
| NSN Approval | Not Declared |
| Civilian/Military | Military |