



## Part Reference Guide

# DR23635T

### Applications

Manufacturer	Model	Series	Position
Boeing	200	737	Main
Boeing	200	757	Main
Boeing	300	737	Main
Boeing	300	757	Main
Boeing	400	737	Main
Boeing	500	737	Main

### Technical Data

Ply Rating	Speed Rating (MPH)	Max Load (lbs)	Tubed/Tubeless	Chined
24	225	33200	Tubeless	No

### Inflation & Dimensions

Size	H40x14.5-19
Inflation Pressure Unloaded PSI	200
Inflation Pressure Loaded PSI	208
Inf Dim Width Shoulder	12.80
Inf Dim Width Max	14.50
Inf Dim Width Min	13.75
Inf Dim OD Min	39.10
Inf Dim OD Max	40
Inf Dim OD Shoulder	36.25
Rim Dim Width Between Flanges	9.50
Rim Dim Ledge Diameter	19
Rim Dim Flange Height	1.40

### Approvals

QTR Number	1237
Test Spec	TSO-C62c
CAA EASA Approval	E14147 20/04/1989
FAA Approval	VK/04/28/1543:89 28/04/89
MOD Approval	DR23635T
NSN Approval	Not Declared
Civilian/Military	Civilian

Rim Dim Min Ledge Width	3.10
-------------------------	------