



Part Reference Guide

DR24221T

Applications

| Manufacturer | Model | Series | Position |
|--------------|-------|------------|----------|
| Bombardier | 100 | DHC Dash 8 | Main |

Technical Data

| Ply Rating | Speed Rating (MPH) | Max Load (lbs) | Tubed/Tubeless | Chined |
|------------|--------------------|----------------|----------------|--------|
| 12 | 160 | 9500 | Tubeless | No |

Inflation & Dimensions

| | |
|---------------------------------|-------------|
| Size | 26.5x8.0-13 |
| Inflation Pressure Unloaded PSI | 150 |
| Inflation Pressure Loaded PSI | 156 |
| Inf Dim Width Shoulder | 7 |
| Inf Dim Width Max | 8 |
| Inf Dim Width Min | 7.55 |
| Inf Dim OD Min | 25.80 |
| Inf Dim OD Max | 26.50 |
| Inf Dim OD Shoulder | 23.80 |
| Rim Dim Width Between Flanges | 6.50 |
| Rim Dim Ledge Diameter | 13 |
| Rim Dim Flange Height | 1 |
| Rim Dim Min Ledge Width | 1.55 |

Approvals

| | |
|-------------------|--------------------------|
| QTR Number | 1004 |
| Test Spec | TSO-C62c |
| CAA EASA Approval | E12845 18/04/1983 |
| FAA Approval | CC/5/16/1479:83 16/05/83 |
| MOD Approval | DR24221T |
| NSN Approval | Not Declared |
| Civilian/Military | Civilian |