



Part Reference Guide

DR24321T

Applications

| Manufacturer | Model | Series | Position |
|--------------|-----------|------------|----------|
| Bombardier | 100 / 200 | DHC Dash 8 | Main |

Technical Data

| Ply Rating | Speed Rating (MPH) | Max Load (lbs) | Tubed/Tubeless | Chined |
|------------|--------------------|----------------|----------------|--------|
| 12 | 190 | 9350 | Tubeless | No |

Inflation & Dimensions

| | |
|---------------------------------|-------------|
| Size | H31x9.75-13 |
| Inflation Pressure Unloaded PSI | 90 |
| Inflation Pressure Loaded PSI | 94 |
| Inf Dim Width Shoulder | 8.30 |
| Inf Dim Width Max | 9.75 |
| Inf Dim Width Min | 9.20 |
| Inf Dim OD Min | 30.10 |
| Inf Dim OD Max | 31 |
| Inf Dim OD Shoulder | 27.70 |
| Rim Dim Width Between Flanges | 6.50 |
| Rim Dim Ledge Diameter | 13 |
| Rim Dim Flange Height | 1 |
| Rim Dim Min Ledge Width | 2.05 |

Approvals

| | |
|-------------------|----------------------------------|
| QTR Number | 1324 |
| Test Spec | TSO-C62d |
| CAA EASA Approval | E15358 21/04/1993 |
| FAA Approval | WEG/VK/04/27/1427:93 30/04/93 |
| MOD Approval | DR24321T |
| NSN Approval | Not Declared |
| Civilian/Military | Civilian |