



Part Reference Guide

DR25821T

Applications

Manufacturer	Model	Series	Position
Boeing	300	737	Aux
Boeing	400	737	Aux
Boeing	500	737	Aux
Boeing	600	737	Aux
Boeing	700	737	Aux
Boeing	800	737	Aux
Boeing	900	737	Aux

Technical Data

Ply Rating	Speed Rating (MPH)	Max Load (lbs)	Tubed/Tubeless	Chined
12	225	9650	Tubeless	No

Inflation & Dimensions

Size	27x7.75-15
Inflation Pressure Unloaded PSI	200
Inflation Pressure Loaded PSI	208
Inf Dim Width Shoulder	6.85
Inf Dim Width Max	7.75
Inf Dim Width Min	7.30
Inf Dim OD Min	26.30
Inf Dim OD Max	27
Inf Dim OD Shoulder	25.40
Rim Dim Width Between Flanges	6
Rim Dim Ledge Diameter	15

Approvals

QTR Number	1154
Test Spec	TSO-C62c
CAA EASA Approval	E13793 08/12/1988
FAA Approval	HH/VK/10/09/2759:87 09/10/87
MOD Approval	DR25821T
NSN Approval	Not Declared
Civilian/Military	Civilian

Rim Dim Flange Height	1
Rim Dim Min Ledge Width	1.65