



Part Reference Guide

DR3633T

Applications

| Manufacturer | Model | Series | Position |
|-------------------|-------|--------|----------|
| McDonnell Douglas | | DC 9 | Aux |

Technical Data

| Ply Rating | Speed Rating (MPH) | Max Load (lbs) | Tubed/Tubeless | Chined |
|------------|--------------------|----------------|----------------|--------|
| 10 | 225 | 6900 | Tubeless | Yes |

Inflation & Dimensions

| | |
|---------------------------------|--------|
| Size | 26x6.6 |
| Inflation Pressure Unloaded PSI | 150 |
| Inflation Pressure Loaded PSI | 156 |
| Inf Dim Width Shoulder | 5.85 |
| Inf Dim Width Max | 6.65 |
| Inf Dim Width Min | 6.25 |
| Inf Dim OD Min | 25.05 |
| Inf Dim OD Max | 25.75 |
| Inf Dim OD Shoulder | 23.55 |
| Rim Dim Width Between Flanges | 5 |
| Rim Dim Ledge Diameter | 14 |
| Rim Dim Flange Height | 1 |
| Rim Dim Min Ledge Width | 1.60 |

Approvals

| | |
|-------------------|------------------------------|
| QTR Number | 1321 |
| Test Spec | TSO-C62d |
| CAA EASA Approval | E15371 28/06/1993 |
| FAA Approval | GH/VK/10/12/2357:93 15/04/93 |
| MOD Approval | DR3633T |
| NSN Approval | Not Declared |
| Civilian/Military | Civilian |