



Part Reference Guide

DR7730T

Applications

Manufacturer	Model	Series	Position
Westland		Sea King	Aux
Westland		LYNX MK9	Aux
Bae Systems (British Aerospace)		Jetstream 31	Aux
Bae Systems (British Aerospace)		Jetstream 32	Aux

Technical Data

Ply Rating	Speed Rating (MPH)	Max Load (lbs)	Tubed/Tubeless	Chined
8	160	2350	Tubeless	No

Inflation & Dimensions

Size	6.00-6
Inflation Pressure Unloaded PSI	55
Inflation Pressure Loaded PSI	57
Inf Dim Width Shoulder	5.35
Inf Dim Width Max	6.30
Inf Dim Width Min	5.90
Inf Dim OD Min	16.80
Inf Dim OD Max	17.50
Inf Dim OD Shoulder	15.45
Rim Dim Width Between Flanges	5
Rim Dim Ledge Diameter	6
Rim Dim Flange Height	0.75
Rim Dim Min Ledge Width	0.85

Approvals

QTR Number	1218
Test Spec	TSO-C62c
CAA EASA Approval	E14106 26/09/1988
FAA Approval	HH/VK/12/22/4233:88 22/12/1988
MOD Approval	DR7730T
NSN Approval	2620-99-7703482/1450645
Civilian/Military	Civilian Or Military

