



Part Reference Guide

DR8628T

Applications

Manufacturer	Model	Series	Position
Shorts	Skyvan	SC.7-3	Aux
Hawker Siddeley		Andover	Aux
Bae Systems (British Aerospace)	Andover	748	Aux

Technical Data

Ply Rating	Speed Rating (MPH)	Max Load (lbs)	Tubed/Tubeless	Chined
8	160	4400	Tubeless	No

Inflation & Dimensions

Size	8.50-10
Inflation Pressure Unloaded PSI	55
Inflation Pressure Loaded PSI	57
Inf Dim Width Shoulder	7.40
Inf Dim Width Max	8.70
Inf Dim Width Min	8.20
Inf Dim OD Min	24.70
Inf Dim OD Max	25.65
Inf Dim OD Shoulder	22.80
Rim Dim Width Between Flanges	6.25
Rim Dim Ledge Diameter	10
Rim Dim Flange Height	0.81
Rim Dim Min Ledge Width	1.15

Approvals

QTR Number	1186
Test Spec	TSO-C62c
CAA EASA Approval	E13941 03/03/1988
FAA Approval	HH/VK/04/1430:88 29/04/1988
MOD Approval	DR8628T
NSN Approval	2620-99-4560855
Civilian/Military	Civilian Or Military