



Part Reference Guide

DZ30730T

Applications

| Manufacturer | Model | Series | Position |
|--------------|-------|--------|----------|
| Atr | | ATR72 | Main |

Technical Data

| Ply Rating | Speed Rating (MPH) | Max Load (lbs) | Tubed/Tubeless | Chined |
|------------|--------------------|----------------|----------------|--------|
| 14 | 190 | 13400 | Tubeless | No |

Inflation & Dimensions

| | |
|---------------------------------|-------------|
| Size | H34x10.0R16 |
| Inflation Pressure Unloaded PSI | 130 |
| Inflation Pressure Loaded PSI | 134 |
| Inf Dim Width Shoulder | 9.35 |
| Inf Dim Width Max | 10.40 |
| Inf Dim Width Min | N/A |
| Inf Dim OD Min | N/A |
| Inf Dim OD Max | 34.85 |
| Inf Dim OD Shoulder | 32.95 |
| Rim Dim Width Between Flanges | 7.00 |
| Rim Dim Ledge Diameter | 16 |
| Rim Dim Flange Height | 1.125 |
| Rim Dim Min Ledge Width | 2.150 |

Approvals

| | |
|-------------------|-------------------|
| QTR Number | 1575 |
| Test Spec | ETSO-C62e |
| CAA EASA Approval | EASA.210.10041235 |
| FAA Approval | - |
| MOD Approval | DZ30730T |
| NSN Approval | N/A |
| Civilian/Military | Civilian |